

# ASSY® 3.0

# ASSY®

			Bifarbe															
Ød mm	l mm	lg mm		Art.-Nr.	Art.-Nr.	Art.-Nr.	Art.-Nr.	dh mm	Art.-Nr.	Art.-Nr.	Art.-Nr.	dh mm	lg mm	Art.-Nr.	VE St.			
5,0	16	11	AW® 20	0170 050 16				9,5				10,0	14,0	0153 050 016	500			
	17													15,0		0153 050 017		
	20	15		0170 050 20		0170 250 20										18,0	0153 050 020	
	25	20		0170 050 25		0170 250 25										22,0	0153 050 025	
	30	25		0170 050 30		0170 250 30										27,0	0153 050 030	
		20			0170 150 30		0170 350 30											
	35	30		0170 050 35		0170 250 35					0154 050 35						32,0	0153 050 035
		20			0170 150 35		0170 350 35											
	40	32		0170 050 40		0170 250 40					0154 050 40			0154 350 40			37,0	0153 050 040
		25			0170 150 40		0170 350 40											
	45	37		0170 050 45		0170 250 45											42,0	0153 050 045
		30			0170 150 45		0170 350 45											
	50	42		0170 050 50		0170 250 50					0154 050 50			0154 350 50			46,0	0153 050 050
		30			0170 150 50		0170 350 50										52,0	0153 050 055
	55	47		0170 050 55		0170 250 55												
		32			0170 150 55		0170 350 55											
	60	52		0170 050 60		0170 250 60					0154 050 60		0154 250 60	0154 350 60			56,0	0153 050 060
		37			0170 150 60		0170 350 60											
	70	62		0170 050 70		0170 250 70							0154 250 70	0154 350 70			66,0	0153 050 070
		42			0170 150 70		0170 350 70											
80	72	0170 050 80		0170 250 80						0154 350 80								
	42		0170 150 80		0170 350 80							42,0	0153 150 080					
90	47		0170 150 90		0170 350 90							46,0	0153 150 090					
100	52		0170 150 100		0170 350 100							52,0	0153 150 100					
110	52		0170 150 110		0170 350 110													
120	62		0170 150 120		0170 350 120													
6,0	30	24	AW® 30	0170 060 30				12,35				12,0			100			
	40	32		0170 060 40		0170 260 40								37,0		0153 060 040		
		24			0170 160 40		0170 360 40											
	45	37		0170 060 45		0170 260 45												
		32																
	50	42		0170 060 50		0170 260 50										46,0	0153 060 050	
		32			0170 160 50		0170 360 50											
	55	45		0170 060 55														
	60	50		0170 060 60		0170 260 60										54,0	0153 060 060	
		37			0170 160 60		0170 360 60											
	70	60		0170 060 70		0170 260 70										64,0	0153 060 070	
		42			0170 160 70		0170 360 70											
	80	70		0170 060 80		0170 260 80										70,0	0153 060 080	
		50			0170 160 80		0170 360 80											
	90	50			0170 160 90		0170 360 90									50,0	0153 160 090	
	100	60			0170 160 100		0170 360 100									60,0	0153 160 100	
	110	70			0170 160 110		0170 360 110											
	120	70			0170 160 120		0170 360 120											
	130	70			0170 160 130		0170 360 130											
	140	70			0170 160 140		0170 360 140											
150	70		0170 160 150		0170 360 150													
160	70		0170 160 160		0170 360 160													
180	70		0170 160 180		0170 360 180													
200	70		0170 160 200		0170 360 200													
220	70		0170 160 220		0170 360 220													
240	70		0170 160 240		0170 360 240													
260	70		0170 160 260		0170 360 260													
280	70		0170 160 280		0170 360 280													
300	70		0170 260 300		0170 360 300													

\* eingängiges Gewinde

**ASSY® 3.0** Ø 4,0-4,5 mm  
**ASSY® 3.0** Ø 5,0-12,0 mm



Mit allgemeiner bauaufsichtlicher Zulassung



Mit allgemeiner bauaufsichtlicher Zulassung



ETA-11/0190