

## SPRAY ADHESIVE



**Fast-drying adhesive for all light-weight materials**

**High thermal stability**

Permanent firm hold for almost all applications

**Fast-drying**

Thanks to fast hardening, working material can already be loaded and processed further after a short time

**Adjustable spraying nozzle**

Optimal for use in an extremely broad range of work situations

**Silicone-free**

<b>Art. No.</b>	<b>0890 100 055</b>	
<b>P. Qty.</b>	1	12
<b>Contents</b>	500 ml	500 ml
<b>Chemical basis</b>	Neoprene-based synthetic rubber	Neoprene-based synthetic rubber
<b>Color</b>	Beige	Beige
<b>Min./max. temperature resistance</b>	-40 to 80 °C	-40 to 80 °C
<b>Suitable for storage from time of manufacture</b>	9 months	9 months

Supplement to Art. No.:	Designation	Art. No.
0890 100 055	Inoclean degreaser	<b>0890 107 500</b>
	Precleaner	<b>0893 200 1</b>
	Silicone remover	<b>0893 222</b>
		<b>0893 222 5</b>
Acetone Cleaner	<b>0893 460</b>	

**Application**

Permanently and quickly bonds plastic, foam, cork, foils, metal, wood, paper and polystyrene with and to each other. Especially suitable in the motor vehicle sector, in plant workshops, in switch cabinet and ventilation system construction etc.

**Instructions**

- Thin application of adhesive; saturate well on absorbent surfaces
- Flash-off time depending on the surface, material and temperature 5-10 minutes.

**Note**

Caution: Not suitable for adhesive bonding of soft PVC and PVC films. After use, turn the can upside down and spray until the nozzle is empty.

With this information, we want to advise you to the best of our knowledge based on our tests and experience. Preliminary testing required! For further information, see the Technical Data Sheet.