

# SUPER RTV SILICONE ADHESIVE AND SEALING COMPOUND



Illustration only

**High-quality adhesive and sealing compound for use in industry and the automotive sector.**

### Excellent resistance to chemicals

- Can also be used in critical areas in which the seal comes into contact with various liquids
- Outstanding resistance to engine oil and transmission oil, refrigerant and anti-freeze agent

### Non-acidic hardening system

- Non-corrosive, therefore has no negative impact on electronic components and on lambda probes

### Sealant in compressed-air can

- Easy to dispense without additional aids
- The fine beads allow the product to be applied uniformly

Art. No.	0893 331 1	0893 331 2	0893 331 3	0893 331 4	0893 331 6
<b>P. Qty.</b>	1/12	1/12	1/12	1/12	1/12
<b>Colour</b>	Black	Red	Blue	Transparent	Grey
<b>Contents</b>	200 ml	200 ml	200 ml	200 ml	200 ml
<b>Chemical basis</b>	Neutral crosslinked silicones, oxime-based	Neutral crosslinked silicones, oxime-based	Neutral crosslinked silicones, oxime-based	Neutral crosslinked silicones, oxime-based	Neutral crosslinked silicones, oxime-based
<b>Min./max. temperature resistance</b>	-60 to 260 °C	-60 to 315 °C	-60 to 260 °C	-60 to 260 °C	-60 to 260 °C
<b>Max. short-term temperature resistance</b>	300 °C	370 °C	300 °C	300 °C	300 °C
<b>Range of applications</b>	Water pumps, Oil pumps, Front cover, Camshaft bearing cover, Thermostat housing, Oil pans, Transmission cover, Sunroof, Doors	Oil pumps, Front cover, Camshaft bearing cover, Oil pans, Transmission cover, Exhaust manifold, Exhaust flange, Cover and flange on engines, Intake area	Oil pans, Valve cover, Rear axle housing, Crankshaft housing, Differential housing, Camshaft bearing cover	Sealing of accumulators, Sealing of halogen lamp, Sealing of vehicle body parts, Sealing of transformer	Water pumps, Oil pumps, Front cover, Camshaft bearing cover, Thermostat housing, Oil pans, Transmission cover, Intake area, Sealing of accumulators

Related products	Art. No.
Nozzle attachment Super RTV silicone	0891 321 001

## Instructions

Optimum adhesion to dry, clean and dust-free surfaces. The old sealant must be removed in full from the surface.

The usage instructions are recommendations based on the tests we have conducted and are based on our experience; carry out your own tests before each application. We do not assume any liability for a specific application result due to the large number of applications and storage and processing conditions. Insofar as our free customer service provides technical information or acts as an advisory service, no responsibility is assumed by this service except where the advice or information given falls within the scope of our specified, contractually agreed service or the advisor was acting deliberately. We guarantee consistent quality of our products. We reserve the right to make technical changes and further develop products.