

BRAKE FLUID DOT 5.1



Exceeds DOT standards.

- For hydraulic brake and clutch systems.
- Wurth DOT 5.1 brake fluid meets and exceeds the current international specifications of US FMVSS 116 DOT 5.1 / DOT 4 / DOT 3, SAE J 1703 / SAE J 1704 and ISO 4925 (Class 3/4/5.1).
- Can be mixed with all brake fluids meeting the same specifications.
- Wurth DOT 5.1 is recommended for use in passenger cars, commercial vehicles and motorcycles with hydraulic brake and clutch systems, where a non-petroleum based fluid is to be used.
- Provides excellent protection against corrosion of iron and non-ferrous metals.
- High thermal stability.
- Will not damage rubber parts. Not suitable for vehicles with mineral or silicone type brake fluids.
- If in doubt, refer to the vehicles manual.

Contents	Art. No.	Pack Qty.
500 ml	0892 950 051	1/24
5 L	0892 009 551	1/4
20 L	0892 009 251	1

Colour	Pale Straw Yellow
Min. Typical Dry Boiling Point	269 °C
Min. Typical Wet boiling point	187 °C
Shelf life from production	36 months
Kinematic Viscosity @ -40 °C	810 cSt
Kinematic Viscosity @ 100 °C	2.16 cSt
Density @20 °C	1.069 g/ml

Notice:

- Keep the brake fluid clean and dry. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs.
- Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture. Moisture will lower the grade of the fluid.
- Do not refill container and do not use for other liquids.
- Dispose of used brake fluid responsibly.
- Brake fluid damages paint work -if spilt wash off immediately with plenty of water.

Application areas:

For Hydraulic Brake and Clutch Systems.

Instructions:

The brake fluid must be changed in the vehicle every 2 years. Follow the recommendations of the vehicle manufacturer when adding or changing the brake fluid.

Dispensing tap for 5 L Art No. 0891423005. (pierce the centre of the foil to insert, removing the foil will cause leakage)..