

ASSY® PLUS 4 VG CSMP TESTA PIANA SVASATA, FI, RW, ACC.ZINC.BIANCO

diametro nominale d [mm]	lunghezza l [mm]	lunghezza filetto lg [mm]	lunghezza filetto con punta b [mm]	diametro testa dh [mm]	altezza testa k [mm]	impronta RW	Art.
6	80	67	67	12	4,4	RW40	0150 106 080
	100	87	87				0150 106 100
	120	107	107				0150 106 120
	140	123	123				0150 106 140
	160	143	143				0150 106 160
	180	163	163				0150 106 180
	200	183	183				0150 106 200
8	120	101	101	15	4,9		0150 108 120
	140	121	121				0150 108 140
	160	141	141				0150 108 160
	180	161	161				0150 108 180
	200	181	181				0150 108 200
	220	201	201				0150 108 220
	240	221	221				0150 108 240
	260	241	241				0150 108 260
	280	261	261				0150 108 280
	300	275	275				0150 108 300
	320	295	295				0150 108 320
	340	315	315				0150 108 340
	360	335	335				0150 108 360
	380	355	355				0150 108 380
	400	375	375				0150 108 400
	430	405	405				0150 108 430
	450	425	425				0150 108 450
480	445	445	0150 108 480				
530	495	495	0150 108 530				
580	545	545	0150 108 580				
12	120	94	94	22,5	7		RW50
	140	114	114			0150 112 140	
	160	134	134			0150 112 160	
	180	154	154			0150 112 180	
	200	174	174			0150 112 200	
	220	194	194			0150 112 220	
	240	214	214			0150 112 240	
	260	219	219			0150 112 260	
	280	239	239			0150 112 280	
	300	259	259			0150 112 300	
	320	279	279			0150 112 320	
	340	299	299			0150 112 340	
	360	319	319			0150 112 360	
	380	339	339			0150 112 380	
	400	359	359			0150 112 400	
	430	389	389			0150 112 430	
	450	409	409			0150 112 450	
480	439	439	0150 112 480				
600	559	559	0150 112 600				

Possibilità di riporre ordinatamente negli scaffali ORSY o nei distributori automatici ORSY MAT

Esempi d'applicazione:

